



CHINA JINWANG ELECTRICAL



10KV-15KV

Type	Rated voltage (KV)	Rated current (A)	Breaking current (A)	Impulse voltage (BIL)	Power-frequency withstand voltage	Leakage distance (mm)	Weight (kg)	Dimensions (cm)
FSC-43	10	100	10000	110	40	380	3.5	39 × 36 × 10.5
FSC-43	10	200	12000	110	40	380	3.5	



24KV-27KV

Type	Rated voltage (KV)	Rated current (A)	Breaking current (A)	Impulse voltage (BIL)	Power-frequency withstand voltage	Leakage distance (mm)	Weight (kg)	Dimensions (cm)
FSC-44	24	100	6000	150	65	620	3.8	40 × 36 × 12
FSC-44	24	200	8000	150	65	620	3.8	



27KV-33KV

Type	Rated voltage (KV)	Rated current (A)	Breaking current (A)	Impulse voltage (BIL)	Power-frequency withstand voltage	Leakage distance (mm)	Weight (kg)	Dimensions (cm)
FSC-45	27	100	6000	170	70	620	7.3	48 × 35 × 12
FSC-45	27	200	8000	170	70	620	7.3	



30KV-33KV

Type	Rated voltage (KV)	Rated current (A)	Breaking current (A)	Impulse voltage (BIL)	Power-frequency withstand voltage	Leakage distance (mm)	Weight (kg)	Dimensions (cm)
FSC-46	33	100	6000	170	70	680	5.3	60 × 35.5 × 12
FSC-46	33	200	8000	170	70	680	5.3	



36KV-38KV

Type	Rated voltage (KV)	Rated current (A)	Breaking current (A)	Impulse voltage (BIL)	Power-frequency withstand voltage	Leakage distance (mm)	Weight (kg)	Dimensions (cm)
FSC-47	36	100	6000	180	75	820	6	66 × 35.5 × 12
FSC-47	36	200	8000	180	75	820	6	



24KV-27KV

Type	Rated voltage (KV)	Rated current (A)	Breaking current (A)	Impulse voltage (BIL)	Power-frequency withstand voltage	Leakage distance (mm)	Weight (kg)	Dimensions (cm)
FSC-48	24	100	6000	150	65	650	5.8	39 × 35 × 11
FSC-48	24	200	8000	150	65	650	5.8	